

**DESCRIPTION**

Ventilation hoods SH type are destined for installation in ventilation systems of seagoing ships as well as offshore objects. They are provided with weather-tight/fire closing device in accordance to SOLAS regulations. SH type hoods are designed for installation on weather decks. Coaming is made of carbon steel St3Sx, painted with set of marine paints, wire gauze is made of stainless steel 316 and spindle of closing device is made of stainless steel. By ordering specify required nominal diameter DN.

**TECHNICAL SPECIFICATION & DIMENSIONS**

DN	Dimensions [mm]													Weight [kg]
	ØA	ØB	C	NxØD	E	F	ØG	H	J	K	L	M	Md	
200	260	290	10	16x12	160	-	400	80	400	90	240	4	M8	27
250	310	340	10	16x12	200	-	500	110	480	110	300	4	M10	38
315	370	405	12	24x12	250	-	630	130	560	140	380	4	M10	48
400	460	490	12	24x12	315	-	800	1730	690	170	470	4	M10	72
500	560	590	12	32x12	350	-	900	210	850	190	610	5	M12	130
560	625	660	12	32x14	400	150	1000	230	820	290	580	5	M12	207
630	695	730	12	48x14	440	170	1150	250	900	340	400	5	M16	280
710	775	810	12	48x14	500	190	1300	280	1000	360	450	5	M16	340
800	865	900	12	64x14	560	220	1500	330	1100	410	500	5	M16	400
900	965	1000	12	64x14	660	245	1650	375	1230	465	560	5	M20	500
1000	1065	1100	12	64x14	700	270	1800	400	1370	520	630	5	M20	550
1120	1205	1250	12	64x14	800	300	2000	435	1500	580	700	5	M20	690
1250	1335	1380	12	64x14	870	330	2300	470	1650	640	800	5	M20	950
1400	1485	1530	12	64x14	980	370	2600	520	1850	720	900	5	M20	1320
1600	1685	1730	12	64x14	1050	400	3000	630	2100	830	1000	5	M20	1710



