

DESCRIPTION

Ventilation hoods EH type are destined for installation in exhaust ventilation systems of seagoing ships as well as offshore objects. They are provided with fire closing device in accordance to SOLAS regulations. EH type hoods are designed for installation on the open decks. Coaming is made of carbon steel St3Sx, painted with set of marine paints, wire gauze is made of stainless steel 316 and shaft bearings of stainless steel. By ordering specify required nominal diameter DN.

TECHNICAL SPECIFICATION & DIMENSIONS

Dimensions [mm]																Weight [kg]	
DN	ØA	ØB	C	NxØD	E	ØF	ØG	H	J	K	P	R	S	L	M		Md
250	310	340	10	16x12	200	410	280	315	230	125	15	12	8	530	4	M10	71
315	370	405	12	24x12	250	510	355	400	290	160	20	12	8	670	4	M10	92
400	460	490	12	24x12	315	650	450	500	365	200	20	15	8	560	4	M10	119
500	560	590	12	32x12	380	810	560	630	460	250	25	15	8	1065	4	M10	182
560	625	660	12	32x14	420	910	630	700	510	280	25	20	10	1200	5	M12	210
630	695	730	12	32x14	470	1020	700	800	570	315	32	20	10	1340	5	M12	280
710	775	810	12	48x14	530	1150	800	890	650	355	32	20	10	1510	5	M12	350
800	865	900	12	48x14	600	1300	900	1000	730	400	40	20	10	1700	5	M12	420
900	965	1000	12	64x14	670	1470	1010	1125	820	450	40	20	10	1910	5	M16	510
1000	1065	1100	12	64x14	740	1625	1125	1250	910	500	50	20	10	2120	5	M16	590
1120	1205	1250	12	64x14	840	1820	1250	1400	1020	560	50	25	10	2380	5	M16	740
1250	1335	1380	12	64x14	940	2030	1400	1560	1140	625	65	25	10	2660	5	M16	1000
1400	1485	1530	12	64x14	1050	2280	1570	1750	1850	710	65	25	10	2950	6	M16	1390
1600	1685	1730	12	64x14	1200	2600	1800	2000	1460	800	80	30	10	3400	6	M16	1820

