

**DESCRIPTION**

Ventilation hoods VH-O type are destined for installation in ventilation systems of special category spaces of ro-ro ships. They are provided with weather-tight/fire closing cover in accordance to SOLAS regulations. VH-O type hoods can be installed in spaces sheltered against sea water splashes. VH-O hoods consist of flanged coaming and cover actuated by pneumatic cylinder fitted on the upper support. Optionally hood may be delivered with limit switches for remote indication of position of cover, in ordinary or non-sparking execution. Coaming is made of carbon steel St3Sx, hot dip galvanized, wire gauze of stainless steel 316 and spindle of closing device is made of stainless steel. By ordering specify required nominal diameter DN.

**TECHNICAL SPECIFICATION & DIMENSIONS**

Dimensions [mm]									Weight [kg]
DN	ØA	ØB	C	NxØD	E	ØG	H	J	
400	460	490	10	12x12	100	700	200	1000	52
500	560	590	12	16x12	120	800	220	1060	59
560	625	660	12	16x14	135	860	235	1120	101
630	695	730	12	16x14	150	930	250	1180	140
710	775	810	12	24x14	165	1010	265	1240	170
800	865	900	12	24x14	180	1100	280	1300	200
900	965	1000	12	32x14	200	1200	295	1360	255
1000	1065	1100	12	32x14	220	1300	310	1420	280
1120	1205	1250	12	32x14	240	1420	330	1480	345
1250	1335	1380	12	32x14	260	1550	350	1540	450

